

COMPRESSION DRIVER

CD-54



Specifications

Throat Diameter	25 mm
Mouth Type	Blot-on
Nominal Impedance	8 Ohm
Power Rating	60 W
Max Power	120 W
Sensitivity	109 dB
Frequency Range	1.1 - 20 KHz
Diaphragm Material	Titanium
Voice Coil Diameter	51 mm
Flux Density	1.75T
Net Weight	2.8 kg

Specifications

Throat Diameter	25 mm
Mouth Type	Screw-on 1.3/8 In
Nominal Impedance	8 Ohm
Power Rating	30 W
Max Power	60 W
Sensitivity	106 dB
Frequency Range	12 - 20 KHz
Diaphragm Material	Titanium
Voice Coil Diameter	34.4 mm
Flux Density	1.45T
Net Weight	941 g

CD-35



Email : nanovaspeaker@yahoo.co.th

facebook : <http://m.facebook.com/nanova.speaker>

fanpage : www.facebook.com/nanovaidolthailand



COMPRESSION DRIVER

Specifications

Throat Diameter	25 mm
Mouthing Type	Screw-on 1.3/8 In
Usable Frequency Range	2K - 18 K
Nominal Impedance	8 Ohm
Power Rating	30 W
Sensitivity	150 dB
Dome Material	Zinc
Voice Coil Material	Flat Wire
Voice Coil Diameter	25.4 mm

NV-108



NEO-11

Specifications

Throat Diameter	25 mm
Mouthing Type	Screw-on 1.3/8 In
Nominal Impedance	8 Ohm
Power Capacity	20 W RMS
Max Power	30 W
Sensitivity	109 dB
Frequency Range	1.5 - 18 KHz
Voice Coil Diameter	25.4 mm
Flux Density	1.44 T
Magnet Type	Neodymium
Over Diameter x Depth	50 x 56.5 mm
Net Weight	0.12 kg



Email : nanovaspeaker@yahoo.co.th

facebook : <http://m.facebook.com/nanova.speaker>

fanpage : www.facebook.com/nanovaidolthailand

